

REFERENCIAS REFERENCES	DESCRIPCIÓN DESCRIPTION
TMS1M5A	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 1 SALIDA HASTA 5A 230VAC SOBRE RELÉ SPDT, AJUSTABLES MEDIANTE MICROSWITCH . ALIMENTACIÓN 12/24 VCC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) OF 1 OUTPUT UP TO 5A 230VAC ON SPDT RELAY, ADJUSTABLE BY MICROSWITCH. 12/24 VDC POWER SUPPLY</i>
TMS1G5A	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 1 SALIDA HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 12/24 VCC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 1 OUTPUT UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 12/24 VDC POWER SUPPLY</i>
TMS2G5A	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 2 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 12/24 VCC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 2 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 12/24 VDC POWER SUPPLY</i>
TMS3G5A	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 3 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 12/24 VCC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 3 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 12/24 VDC POWER SUPPLY</i>
TMS4G5A	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 4 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 12/24 VCC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 4 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 12/24 VDC POWER SUPPLY</i>
TMS1G5M	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 1 SALIDA HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 230 VAC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 1 OUTPUT UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 230 VAC POWER SUPPLY</i>
TMS2G5M	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 2 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 230 VAC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 2 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 230 VAC POWER SUPPLY</i>
TMS3G5M	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 3 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 230 VAC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 3 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 230 VAC POWER SUPPLY</i>
TMS4G5M	TEMPORIZADOR ENTRE 1" (SEG) Y 60' (MIN) DE 4 SALIDAS HASTA 5A 230 VAC SOBRE RELÉS SPDT ENCADENABLES Y AJUSTABLES MEDIANTE POTENCIÓMETROS. ALIMENTACIÓN 230 VAC <i>TIMER BETWEEN 1" (SEC) AND 60' (MIN) FROM 4 OUTPUTS UP TO 5A 230 VAC ON SPDT RELAYS THAT CAN BE CHAINED AND ADJUSTED BY POTENTIOMETERS. 230 VAC POWER SUPPLY</i>



DESDE 1987 OFRECIENDO CALIDAD
SINCE 1987 DELIVERING QUALITY
WWW.DETRONIC.ES